Perfect Nails Fast Dry Top Coat

SDS DATE:03/01/2022

#### **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** Perfect Nails Fast Dry Top Coat

**SYNONYMS:** Nail Polish

MANUFACTURER: Beautyworld Pty Ltd

ADDRESS: Unit 2 /33-35 Lundberg Dr, Murwillumbah, NSW, 2484 Australia

**PHONE:** 1300 739893 ( Business Hours)

**AFTER HOURS:** 0414362966 **FAX PHONE:** 02 66 725265

EMAIL: <a href="mailto:info@beautyworld.com.au">info@beautyworld.com.au</a>
WEB: <a href="www.beautyworld.com.au">www.beautyworld.com.au</a>

CHEMICAL NAME: Mixture
CHEMICAL FAMILY: Mixture
PRODUCT USE: Nail lacquer

#### **SECTION 2: HAZARDS IDENTIFICATION**





#### **Hazardous Nature**

This product is classified as hazardous under GHS for Australian criteria

#### **Hazardous Classification**

Flammable Liquids: 2; Acute Toxicity - Oral:3; Skin Corrosion/Irritation: 3; Serious Eye Damage/Irritation: 2A

#### **Hazardous Statement**

Highly Flammable liquid and vapour

### **Hazard Statements**

H225: Highly flammable liquid and vapour

H319: Causes serious eye irritation

AUH066: Repeated exposure may cause skin dryness or cracking

H336: May cause drowsiness or dizziness

### **Precautionary Statements**

P102: Keep out of reach of children.

P403+235: Store in a well ventilated place. Keep cool

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P262: Do not get in eyes, on skin or on clothing.

P273: Avoid release to the environment

P242+243: Use only non sparking tools. Take precautionary measures against static discharge

P370+ 378: In case of fire: Use sand, earth or chemical foam to extinguish.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P303+361+353: IF ON SKIN: Remove contaminated clothing and wash skin with soap and water.

Perfect Nails Fast Dry Top Coat

SDS DATE:03/01/2022

### SECTION 2: HAZARDS IDENTIFICATION (cont)

P501: Dispose of contents/container according to local regulations.

Dangerous Goods Classification: 3, Poisons Schedule: Not regulated

#### **SECTION 3: COMPOSITION**

Ingredient	CAS	Percentage	
Ethyl Acetate	141-78-6	50-75%	
N Butyl Acetate	123-86-4	10-25%	
Isopropanol	67-63-0	1-5%	

#### **SECTION 4: FIRST AID MEASURES**

### For advice, contact Poisons Information Centre (Phone Australia: 13 1126) or a doctor.

### Ingestion

If swallowed, DO NOT induce vomiting. Keep at rest. Seek immediate medical attention.

#### **Eve Contact**

Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.

#### **Skin Contact**

Flush area with large amounts of water and wash area with soap if available. Remove contaminated clothing, including shoes, and launder before reuse. Seek medical attention for skin irritations.

#### Inhalation

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Seek immediate medical attention.

#### **First Aid facilities**

Provide eye baths and safety showers.

#### **Medical Attention**

Treat according to symptoms. Avoid gastric lavage: risk of aspiration of product to the lungs with the potential to cause chemical pneumonitis

### **SECTION 5: FIRE-FIGHTING MEASURES**

### HAZCHEM CODE: 3YE

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing firefighters with this Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

#### Suitable extinguishing media

Dry chemical or alcohol foam

## Hazards from combustion products

Carbon dioxide, carbon monoxide

### Precautions for fire fighters and special protective equipment

Fully self-contained breathing aparatus, overalls, and safety boots

SDS DATE:03/01/2022

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### **Emergency Procedures**

Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum. Prevent vapours from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.

### Methods and materials for containment

### **Major Land Spill**

- Warn occupants of downwind areas of possible fire and explosion hazard.
- □ Prevent liquid from entering sewers, watercourses, or low-lying areas.
- □ Shut off the source of the spill if possible and safe to do so.
- □ Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.
- □ Take measures to minimise the effect on the ground water.
- □ Contain the spilled liquid with sand or earth.
- □ Recover by pumping use explosion proof pump or hand pump or with a suitable absorbent material.
- □ Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- □ See "First Aid Measures" and "Stability and Reactivity"

## **Major Water Spill**

- □ Eliminate any sources of ignition.
- Warn occupants and shipping in downwind areas of possible fire and explosion hazard.
- □ Notify the port or relevant authority and keep the public away from the area.
- □ Confine the spill if possible.
- □ Remove the product from the surface by skimming or with suitable absorbent material.
- □ Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- □ See "First Aid Measures" and "Stability and Reactivity".

#### **SECTION 7: HANDLING AND STORAGE**

### Precautions for handling

This product is flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Use grounding leads to avoid discharge (electrical spark).

## Conditions for safe storage

Store in a cool, dry place away from direct sunlight. Do not pressurise, cut, heat or weld containers - residual vapours are flammable. This product is flammable and will fuel a fire in progress.

#### Incompatible materials

Natural Rubber, Butyl Rubber, EPDM, Polystyrene

SDS DATE:03/01/2022

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### **National Exposure Standards**

Ethyl acetate: TWA 720mg/m3 ( 200ppm), STEL 1440mg/mg ( 400ppm) N Butyl Acetate: TWA 713mg/m3 ( 150ppm), STEL 950mg/m3 ( 200ppm) Isopropanol: TWA 983mg./m3 ( 400ppm), STEL 1230mg/m3 ( 500ppm)

The time weighted average concentration (TWA) is the highest allowable exposure concentration in an eight-hour day for a five-day working week. The short-term exposure limit (STEL) is the maximum allowable exposure concentration at any time.

### **Biological limit values**

Not available

### **Engineering Controls: Ventilation**

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a fume hood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

# **Personal Protective Equipment**

**Respiratory Protection:** Where concentrations in air may exceed the limits described in the National Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product.

**Eye Protection:** Always use safety glasses or a face shield when handling this product.

**Skin/ Body Protection:** Always wear long sleeves and long trousers or coveralls, and enclosed footwear or safety boots when handling this product. It is recommended that chemical resistant gloves (e.g. PVC) be worn when handling this product.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Property	Unit of Measurement	Value		
Appearance	Visual	Opaque to Clear liquid		
Boiling Point/ Range	°C	From 77		
Flash Point	°C	-4		
Density @ 15°C	g/ml	0.87		
Vapour Pressure @ 20°C	kPa	No data		
Explosive Limits (LEL - UEL)	%	N Butyl Acetate 1.7-7.6		
		Ethyl Acetate 2 – 11.4,		
		Isopropanol 1-8 - 12		
Vapour Density @ 20°C	kPa	No data		
Autoignition Temperature	°C	No data		
Viscosity @ 20°C	cSt	No data		
Percent Volatiles	%	70-80		
Solubility with Water	% w/w	Partly soluble		

Perfect Nails Fast Dry Top Coat

SDS DATE:03/01/2022

#### **SECTION 10: STABILITY AND REACTIVITY**

### **Chemical Stability**

Stable at room temperature and pressure

#### Conditions to avoid

Sources of heat and ignition, open flames.

### Hazardous decomposition products

Carbon monoxide, carbon dioxide and other organic complexes on incomplete burning or oxidation.

#### **Hazardous reactions**

Oxidizing agents, mineral acids, halogenated organic compounds, chloroform and alkalis

#### **Hazardous Polymerisation**

Will not occur

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### **Acute Effects**

### Ingestion

This product is harmful by ingestion. Large amounts of this product will result in central nervous system effects such as: headaches, dizziness, hallucinations, euphoria, tingling of the extremities, vomiting, and possibly loss of consciousness.

## Eye Contact

High vapour concentrations produce conjunctiva irritation. This product can cause corneal burns.

#### Skin Contact

This product is easily absorbed to the skin and produces dryness and cracking after prolonged contact.

### Inhalation

High vapour concentrations are irritating to respiratory system producing central nervous system effects such as dizziness, headaches, nausea, vomiting and loss of appetite.

#### **Chronic Effects**

This product is an experimental teratogen and affects the peripheral nervous system (arms and legs). People with pre-existing liver or kidney disfunction should limit exposure to this product.

### **Other Health Effects Information**

The effects of this product in combination with n-hexane are potentiated (greatly increased). This means that the effects suffered by ingestion or inhalation will be increased, or experienced more quickly.

## **Toxicological Information**

Oral LD<sub>50</sub>: n Butyl Acetate: 10768 mg/kg (oral, rat)

Dermal TCLo: n Butyl Acetate Inhal: LC50 (rat): 390 ppm/4hr; Skin: LD50 (rabbit): > 17600 mg/kg

Oral LD $_{50}$ : Isopropanol: 5045 mg/kg (oral, rat) TDLo: Isopropanol 223 mg/kg (oral, human) Oral LD $_{50}$ : Ethyl acetate 6100 mg/kg (rat)

Dermal TC<sub>I O</sub>: Ethyl acetate Inhalation: 1600 ppm/8hr (rat)

Perfect Nails Fast Dry Top Coat

SDS DATE:03/01/2022

#### **SECTION 12: ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data for this product, but data for components is listed below.

### **Ethyl Acetate - Aquatic Toxicity**

Fish Toxicity (rainbow trout, goldfish, bluegill): LC<sub>50</sub>(96hr): Rainbow Trout: 2600000 μg/L

Daphnia Magna EC<sub>50</sub> (24 hr): LC<sub>50</sub>: 175000 μg/L

Blue-green algae (Toxicity threshold 7-8 days): LO<sub>EC</sub>: 150000 μg/L Green algae (Toxicity threshold 7-8 days): LO<sub>EC</sub>: 5500000 μg/L

#### N Butyl Acetate - Aquatic Toxicity

Fish Toxicity (rainbow trout, goldfish, bluegill): LC50(96hr): Bluegill: 100000 µg/L

Daphnia Magna EC50 (24 hr): LC50: 205000 μg/L

Blue-green algae (Toxicity threshold 7-8 days):LOEC: 420000 µg/L

Green algae (Toxicity threshold 7-8 days):

LOEC: 21000 µg/L

## **Isopropanol - Aquatic Toxicity**

Fish Toxicity (rainbow trout, goldfish, bluegill): LC<sub>50</sub>(96hr): Based on data for a similar component or

preparation, this product is expected to be toxic to aquatic

organisms.

Daphnia Magna EC<sub>50</sub> (24 hr): No data available

Daphnia Magna EC<sub>50</sub> (48 hr): Long term adverse effects to aquatic organisms are possible

if continuous exposure is maintained.

Blue-green algae (Toxicity threshold 7-8 days):

Green algae (Toxicity threshold 7-8 days):

No data available

No data available

#### Persistence/ degradability

Volatilises in air

### **Mobility**

This product is highly volatile and is expected to rapidly evaporate to the air if released into the water

### **SECTION 13: DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry.

# Special Precautions for Landfill or Incineration

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

SDS DATE:03/01/2022

#### **SECTION 14: TRANSPORT INFORMATION**

Road & Rail		Maritime		Air	
UN Number	1263	UN Number	1263	UN Number	1263
Proper Shipping name	Paint	Proper Shipping name	Paint	Proper Shipping name	Paint
DG Class	3	DG Class	3	DG Class	3
Sub Risk	None	Sub Risk	None	Sub Risk	None
Packing group	II	Packing group	II	Packing group	II
Hazchem	3YE	Hazchem	3YE	Hazchem	3YE

# **Dangerous Goods Segregation**

This product is classed as Dangerous Goods Class 3, packing group II. Please consult the Australian Dangerous Goods Code for Transport by Road and Rail for information.

#### **SECTION 15: REGULATORY INFORMATION**

Country/ Region: Australia

Inventory: AICS Status: Listed

Poisons Schedule: Not regulated

SECTION 16: OTHER INFORMATION

Reasons for Issue: Upgrade to GHS SDS;

**Abbreviations:** 

AICS: Australian Inventory of Chemical Substances

CAS Number: Chemical Abstracts Number

IARC: International Agency for Research on Cancer NOHSC: National Occupational Health and Safety Council

References:

#### **Supplier SDS**

http://chem.sis.nlm.nih.gov/chemidplus http://hsis.ascc.gov.au/SearchHS.aspx

Ecotoxicology data: http://cfpub.epa.gov/ecotox/quick\_query.htm

Sax's Dangerous Properties of Industrial Materials, Richard J. Lewis Snr., pub. Canada (2000)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact Beautyworld Pty Ltd.